



Product Name: Antifoam RK-530T

RK-530T is aqueous emulsion of silicone oil and hydrophobic particles.

Product Applications

Added in textile dyeing process

Internal addition of textile auxiliaries

Product property:

Good compatibility with the system

Suitable for a wide pH range and temperature range

Easy to disperse in water

Main physical and chemical properties:

Item	Index
Appearance	White or yellowish milky liquid
Solid Content	(29-31) %
pH Value	6.0 - 9.0
Viscosity(25°C)	2000~10000mPa·s

Application Process:

Directly added for use, also can be diluted for a low content use.

It can be diluted directly with water, and needs to be used immediately. If it needs to be stored for a certain time after diluted, please consult us for a professional dilution method.

Addition amount 10~1000ppm, and the best addition amount depends on the actual situation on site.

LIMITATIONS

This product is neither tested nor represented as suitable for medical or pharmaceutical uses

Information of manufacturers and products

Product name	Antifoam
Model	RK-530T
Manufacturer	Xiamen Rickman Chemical Technology CO., Ltd. Add: No1267Qianpu South Road, Siming District, Xiamen City, Fujian Province, China
Tel/Fax	0086 15359255189



Product content

Pure or mixture	Mixture
English name	silicone oil and hydrophobic particles.

Precautions

There are no fatal or harmful ingredients to the human body, but try not to touch it directly. If it accidentally gets into the eyes, rinse with clean water.

Storage at room temperature (5-40°C), away from direct sunlight.

Refer to the product's Material Safety Data Sheet (MSDS) before use.

Packaging & Storage

Package	25kg/50kg/200kg plastic drum or 1000kg IBC
Warranty period	6 months (cool and dry place at room temperature)

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained here is offered in good faith and is believed to be accurate. However, because conditions and methods of use of Rickman products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end application.